



**LIGHTING FIXTURE SCHEDULE**

TYPE	MANUFACTURER	MODEL NUMBER	DESCRIPTION	LAMP	DELIVERED LUMENS	L70	WATTS	VOLTAGE	EQUALS
E1	SURELITES	EU-5-70-1-R	WALL MOUNTED EXIT - SINGLE FACE. MATCH EXISTING BUILDING STANDARD.					120 V	DUAL-LITE, LITE ALARMS
E2	SURELITES	EU-5-70-2-R	SUSPENDED EXIT - DUAL FACE. MATCH EXISTING BUILDING STANDARD.					120 V	DUAL-LITE, LITE ALARMS
PA	PRUDENTIAL	P4040-LED35-10-FWA-CC-D1-SC-UNV-CA144-X3-DM10	SUSPENDED 4" DIAMETER "DRUM" LED PENDANT w/ FLAT BOTTOM OPAL ACRYLIC LENS. CUSTOM COLOR PERIMETER BAND. AIR-CRAFT CABLE SUSPENSION FROM STRUCTURE THRU OPENING IN ARCHITECTURAL CEILING. INTEGRAL 0-10v DIMMABLE DRIVER.	LED/3500k	9200 lm	50,000	88 W	120 V	IMPACT LTG, FOCAL POINT
PA2	PRUDENTIAL	P4040-LED35-MED-FWA-CC-D9-SC-UNV-CA144-X3-ND	SUSPENDED 4" DIAMETER "DRUM" LED PENDANT w/ FLAT BOTTOM OPAL ACRYLIC LENS. CUSTOM COLOR PERIMETER BAND. 70% DIRECT/ 30% INDIRECT DISTRIBUTION. AIR-CRAFT CABLE SUSPENSION w/ BOTTOM OF FIXTURE LEVEL @ 10'-0" AFF. NON-DIMMABLE.	LED/3500k	11500 lm	50,000	110 W	120 V	IMPACT LTG, FOCAL POINT
PB	PRUDENTIAL	HSS-LED35-MO-8-SAL-YXX-UNV-CA96-X3-DM10	8' LONG LINEAR LED PENDANT w/ BOTTOM 3-SIDED OPAL ACRYLIC LENS. NATURAL ALUMINUM COLORED HOUSING. INTEGRAL 0-10v DIMMABLE DRIVER. AIR-CRAFT CABLE SUSPENSION w/ BOTTOM OF FIXTURE @ 10'-0" AFF.	LED/3500k	5000 lm	50,000	48 W	120 V	NO EQUALS
PC-4	METALLUX	4SNLED-LD4-30SL-LN-UNV-L835-CD1-U	4' LONG LED INDUSTRIAL STRIP w/ LIGHTLY FROSTED BOTTOM LENS. SUSPEND FIXTURE @ 10'-0". COORDINATE MOUNTING LOCATIONS WITH EQUIPMENT RACKS AND OTHER TRADES IN MECHANICAL ROOMS.	LED/3500k	3052 lm	50,000	25 W	120 V	LITHONIA, ILP
PC-6	METALLUX	6SNLED-LD4-75SL-LN-UNV-L835-CD1-U	6' LONG LED INDUSTRIAL STRIP w/ LIGHTLY FROSTED BOTTOM LENS. SUSPEND FIXTURE @ 10'-0". COORDINATE MOUNTING LOCATIONS WITH EQUIPMENT RACKS AND OTHER TRADES IN MECHANICAL ROOMS.	LED/3500k	7620 lm	50,000	65 W	120 V	LITHONIA, ILP
PD	PRUDENTIAL	HSS-LED35-MO-14-SAL-YXX-UNV-CA96-X3-DM10	14' LONG LINEAR LED PENDANT w/ BOTTOM 3-SIDED OPAL ACRYLIC LENS. NATURAL ALUMINUM COLORED HOUSING. INTEGRAL 0-10v DIMMABLE DRIVER. AIR-CRAFT CABLE SUSPENSION w/ BOTTOM OF FIXTURE @ 10'-0" AFF.	LED/3500k	8750 lm	50,000	77 W	120 V	NO EQUALS
PE	PRUDENTIAL	(4) HSS-LED35-MO-4-SAL-YXX-UNV-CA96-X3-DM10-MOD	(4) 4' LONG LINEAR LED PENDANT IN "X" CONFIGURATION. PROVIDE FOUR INDIVIDUAL FIXTURES AND CENTER NON-ILLUMINATED "X" FOR JOINING FIXTURES IN THE FIELD. BOTTOM 3-SIDED OPAL ACRYLIC LENS. NATURAL ALUMINUM COLORED HOUSING. INTEGRAL 0-10v DIMMABLE DRIVER. AIR-CRAFT CABLE SUSPENSION w/ BOTTOM OF FIXTURE @ 10'-0" AFF.	LED/3500k	10000 lm	50,000	96 W	120 V	NO EQUALS
PF	PRUDENTIAL	(4) HSS-LED35-MO-4-SAL-YXX-UNV-CA96-X3-MOD	(4) 4' LONG LINEAR LED PENDANT IN "X" CONFIGURATION. PROVIDE FOUR INDIVIDUAL FIXTURES AND CENTER NON-ILLUMINATED "X" FOR JOINING FIXTURES IN THE FIELD. BOTTOM 3-SIDED OPAL ACRYLIC LENS. NATURAL ALUMINUM COLORED HOUSING. INTEGRAL NON-DIMMING DRIVER. AIR-CRAFT CABLE SUSPENSION w/ BOTTOM OF FIXTURE @ 10'-0" AFF.	LED/3500k	10000 lm	50,000	96 W	120 V	NO EQUALS
RA	USA1	3021-AC1-5-01/LRTD4-9024-C3-35K5-50-FT-120-DIML2-CB52	RECESSED 4" APERTURE LED DOWNLIGHT w/ CLEAR ALZAK TRIM AND CONE. LOW PROFILE HOUSING w/ MAXIMUM DEPTH OF 4". 1" DEEP CONE, SOLITE LENS AND 50deg MEDIUM DISTRIBUTION. INTEGRAL 0-10v DIMMABLE DRIVER TO 10%.	LED	1925 lm	50,000	19 W	120 V	PRESCOLITE, GOTHAM
RA2	USA1	3021-AC1-5-01/LRTD4-9024-C3-35K5-50-FT-120-DIML2-CB52	RECESSED 4" APERTURE LED DOWNLIGHT w/ CLEAR ALZAK TRIM AND CONE. LOW PROFILE HOUSING w/ MAXIMUM DEPTH OF 4". 1" DEEP CONE, SOLITE LENS AND 50deg MEDIUM DISTRIBUTION. INTEGRAL 0-10v DIMMABLE DRIVER TO 10%.	LED	1446 lm	50,000	19 W	120 V	PRESCOLITE, GOTHAM
RB	USA1	3021-AC1-5-01/LRTD4-9024-C3-35K5-90-FT-120-DIML2-CB52	RECESSED 4" APERTURE LED DOWNLIGHT w/ CLEAR ALZAK TRIM AND CONE. LOW PROFILE HOUSING w/ MAXIMUM DEPTH OF 4". 1" DEEP CONE, SOLITE LENS AND 50deg WIDE DISTRIBUTION. INTEGRAL 0-10v DIMMABLE DRIVER TO 10%.	LED/3500k	1759 lm	50,000	22 W	120 V	PRESCOLITE, GOTHAM
SA	ACOLYTE	RB244-441-6" w/ AC1 EXTRUSION	8' LONG LED TAPELIGHT PRODUCT MOUNTED IN ALUMINUM CHANNEL. FIXTURE IS LOCATED INSIDE OF ACRYLIC WALL - REFER TO ARCHITECTURAL DETAIL FOR MOUNTING LOCATIONS. PROVIDE REMOTE DRIVERS CAPABLE OF POWERING MULTIPLE RUNS. LOCATE DRIVER IN ACCESSIBLE LOCATION OUT OF VIEW.	LED/4000k	345 lm	50,000	32 W	120 V	JESCO, MODALITE
SB	ACOLYTE	RB244-441-17" w/ AC1 EXTRUSION	17' LONG LED TAPELIGHT PRODUCT MOUNTED IN ALUMINUM CHANNEL. FIXTURE IS LOCATED INSIDE OF ACRYLIC WALL - REFER TO ARCHITECTURAL DETAIL FOR MOUNTING LOCATIONS. PROVIDE REMOTE DRIVERS CAPABLE OF POWERING MULTIPLE RUNS. LOCATE DRIVER IN ACCESSIBLE LOCATION OUT OF VIEW.	LED/4000k	345 lm	50,000	68 W	120 V	JESCO, MODALITE
SD	EATON	MT125 LAMP: SORAA SP38-18-25D-930-03	J-BOX MOUNTED METAL ADJUSTABLE LAMP HOLDER. BRONZE FINISH. PROVIDE RETROFIT LED LAMP AS SCHEDULED. UTILIZE RECESSED RETROFIT STYLE JUNCTION BOX RECESSED ABOVE EXISTING DRYWALL.	LED/3000k	900 lm	50,000	18 W	120 V	HUBBELL, STONCO
TA	TECH LIGHTING	700UCF-19-9-5-W-LED	2' LONG UNDERCABINET TASK LIGHT. WHITE FINISH. HARD WIRE FIXTURE w/ CONCEALED FLEX CONDUIT UNDER CABINETS. INTEGRAL ROCKER SWITCH CONTROL.	LED/3500k	693 lm	50,000	11 W	120 V	BRUJCK
TA-3	TECH LIGHTING	700UCF-31-9-5-W-LED	3' LONG UNDERCABINET TASK LIGHT. WHITE FINISH. HARD WIRE FIXTURE w/ CONCEALED FLEX CONDUIT UNDER CABINETS. INTEGRAL ROCKER SWITCH CONTROL.	LED/3500k	1224 lm	50,000	18 W	120 V	BRUJCK
WA-8	PRUDENTIAL	P40-LED35-MO-8-YXX-AWW-D1G-SC-UNV-WB-DM10	8' LONG WALL MOUNTED LINEAR LED FIXTURE w/ WALL GRAZING OPTIC. WALL BRACKET FOR 2" OFF-SET FROM WALL. NATURAL ALUMINUM COLORED HOUSING. INTEGRAL 0-10v DIMMABLE DRIVER.	LED/3500k	4800 lm	50,000	56 W	120 V	A-LIGHT, PEERLESS
WA-12	PRUDENTIAL	P40-LED35-MO-12-YXX-AWW-D1G-SC-UNV-WB-DM10	12' LONG WALL MOUNTED LINEAR LED FIXTURE w/ WALL GRAZING OPTIC. WALL BRACKET FOR 2" OFF-SET FROM WALL. NATURAL ALUMINUM COLORED HOUSING. INTEGRAL 0-10v DIMMABLE DRIVER.	LED/3500k	7200 lm	50,000	96 W	120 V	A-LIGHT, PEERLESS
WB	EATON	MT125 LAMP: SORAA SP38-18-36D-840-03	J-BOX MOUNTED METAL ADJUSTABLE LAMP HOLDER. BRONZE FINISH. PROVIDE RETROFIT LED LAMP AS SCHEDULED. MOUNT TO SURFACE MOUNTED JUNCTION BOX IN WELL OF SKYLIGHT AIMED STRAIGHT DOWN.	LED/4000k	900 lm	50,000	18 W	120 V	HUBBELL, STONCO
WC	SHAPER	689-W-PAR/1/150-120-NA-PFB/ LAMP: SORAA SP38-18-25D-930-03	SURFACE MOUNTED MEDIUM BASE LAMP HOLDER w/ ALUMINUM RING AND BOTTOM HEX CELL LOUVER. FOR EACH LOCATION OF THIS TYPE, PROVIDE (2) FIXTURES BACK TO BACK IN VERTICAL ORIENTATION. INSTALL ON SURFACE MOUNTED 4" BOXES WITH ONE FIXTURE AIMED UP AND ONE FIXTURE AIMED DOWN. INSTALL BOTTOM OF LOWER FIXTURE AT 10'-0" AFF.	LED/3000k	339 lm	50,000	8 W	120 V	NO EQUAL